

**Manufacturer:**

Max Birt Sawmills Limited
155 State Highway 2, Pokeno &
364C Lumsden Road, Ohinewai
P O Box 120, Pokeno, New Zealand
Phone: (09) 294 7800
NZBN: 9429040393711
www.maxbirtawmills.co.nz
sales@maxbirt.co.nz



Building Product Information Sheet

This sheet is produced in compliance with the requirements of the *Building (Building Product Information Requirements) Regulations 2022*. Under Schedule 1 of those regulations certain information must be disclosed about designated building products (in this case **New Zealand Non-Structural Timber of Radiata Pine**) to provide building product users with data about how building products contribute to compliance with the Building Code.

Product: New Zealand Non-Structural Timber of Radiata Pine

Product & Intended Use:

Timber produced from solid wood and used in construction where structural timber is not required. Examples of typical uses are (measurements in mm unless otherwise stated):

Ceiling Strapping – solid timber in sizes 70 x 35 and 140 x 35 and treated to H1.2 kiln dried.

Cavity batten – solid timber in sizes 45 x 20 and treated to H3.1 kiln dried or H3.2 kiln dried.

Tile batten, solid timber in sized 50 x 40 and 50 x 50 and treated to H1.2 wet.

Product Identifier:

Ceiling strapping is end branded on each piece with the treatment details. Cavity and Tile battens are perimeter branded on each packet only with the treatment.

Hazard Class:

Treatments are usually H1.2, H3.1 & H3.2 as detailed above for each product.

Relevant Building Code clauses:

B2 Durability.

Contribution to compliance:

B2 Durability – compliance is via B2/AS1 Section 3.0 Generic Materials clause 3.2 Timber and wood based building products.

Building Product Limitations:

All products are for non-structural building applications.

Installation requirements:

When a treated timber product is cut, notched, drilled, or worked in any way that breaks the surface of the timber product, then it is recommended that a suitable resealing preservative product be applied to the exposed areas to maintain the treatment integrity.

Maintenance requirements:

Ensure that kiln dried timber, particularly untreated timber or timber treated to H1.2, is not exposed to continuous wetting or subject to high levels of moisture especially when used in applications that are hidden from clear view or are or are not readily accessible for regular inspection.

Declaration:

Non-structural timber is not subject to a warning or ban in terms of S26 of the *Building Act 2004*.

This document has been developed for industry and uncontrolled after distribution. Please see www.maxbirtssawmills.co.nz or contact Max Birt Sawmills Limited for original version.

Date: 1/11/2023